

Huebsch is the answer.



OPL
Flatwork Finishers



Flatwork Finisher Specifications

Models	UD08F055	UD13F063	UD13F079	UD20F075	UD20F098	UD20F126
Roll Diameter - in (mm)	8" (200)	13" (325)	13" (325)	20" (500)	20" (500)	20" (500)
Finishing Width - in (mm)	55" (1400)	63" (1600)	78" (2000)	75" (1900)	98" (2500)	126" (3200)
Ironing Speed - ft/m (m/m)	3-15 (1-4.5)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)
Overall Dimensions* L" x D" x H" - in (mm)	74" x 17 1/2" x 43 3/4" (1880 x 445 x 1110)	86" x 26" x 43 13/16" (2192 x 660 x 1112)	100 1/8" x 26" x 43 13/16" (2542 x 660 x 1112)	117 1/8" x 42 1/4" x 46 1/8" (2975 x 1072 x 1171)	140 3/4" x 42 1/4" x 46 1/8" (3574 x 1072 x 1171)	168 5/16" x 42 1/4" x 46 1/4" (4275 x 1072 x 1171)
Roll Motor - HP (kW)	.33 (.25)	.33 (.25)	.33 (.25)	.5 (.37)	.5 (.37)	.5 (.37)
Roll Exhaust Motor - HP (kW)	1 x .12 (.09)	2 x .16** (2 x .12**)	2 x .16 (2 x .12)	2 x .34*** (2 x .25***)	2 x .34 (2 x .25)	2 x .34 (2 x .25)
Roll Exhaust Duct - in (mm)	1 x 3.25" (83)	2 x 4**** (2 x 98**)	2 x 4" (2 x 98)	2 x 6**** (2 x 300****)	2 x 6" (2 x 300)	2 x 6" (2 x 300)
Gas Heating						
Maximum Gas Input - Btu (kW)	N/A	76,792 (23)	102,340 (30)	136,453 (40)	187,623 (55)	235,495 (69)
Gas Inlet - in (mm)	N/A	3/4" (12.7)	3/4" (12.7)	1" (14)	1" (14)	1" (14)
Electrical Requirements	120/60/1	N/A	15	15	15	15
• Circuit Breaker	230/50/3	N/A	6	6	6	6
	400/50/3	N/A	6	6	6	6
Electric Heating						
Capacity Resistances - HP (kW)	14 (10.5)	21 (16)	27 (20)	42 (31.5)	54 (40.5)	72 (54)
Electrical Requirements	208-240/60/3	40	50	63	N/A	N/A
• Circuit Breaker	230/50/3	40	50	63	100	125
	400/50/3	25	32	40	63	100
Steam Heating						
Steam Inlet - in (mm)	N/A	N/A	N/A	3/4" (19.5)	3/4" (19.5)	3/4" (19.5)
Condensate Return - in (mm)	N/A	N/A	N/A	1/2" (12.7)	1/2" (12.7)	1/2" (12.7)
Hourly Consumption - lb/hr (kg/hr)	N/A	N/A	N/A	110 (50)	147 (67)	187 (85)
Min.-Max Steam Pressure - psi (bar)	N/A	N/A	N/A	145 (10)	145 (10)	145 (10)
Electrical Requirements	120/60/1	N/A	N/A	15	15	15
• Circuit Breaker	230/50/3	N/A	N/A	4	4	4
	400/50/3	N/A	N/A	4	4	4
Shipping Weight - lb (kg)	418 (190)	1345 (610)	1455 (660)	2167 (984)	2796 (1269)	3421 (1553)
Agency Approvals	Elec Gas	ETL _{US} , CE N/A	ETL _{US} , CE CSA Star, CSA Flame, CE	ETL _{US} , CE CSA Star, CSA Flame, CE	ETL _{US} , CE CSA Star, CSA Flame, CE	ETL _{US} , CE CSA Star, CSA Flame, CE

* Removal of trays will allow 32" door access on all models.

** One motor on electric models.

*** One motor on steam models.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A. ©Copyright 2009 Alliance Laundry Systems LLC

Quality Product, Quality Results

My laundry demands efficiency, productivity and high quality finished results. How can Huebsch meet my needs?

Quality by design.

Our heated cylinder finishers are equipped with a frequency-controlled motor, suspended roll and Nomex ironing belts to deliver top-of-the-industry results.

Total control.

Huebsch's versatile microprocessor control enables you to store temperature and speed settings to ensure consistent, top quality results. Temperatures can be set between 176 and 350 degrees, while there are seven speed settings.



The right sizes.

Huebsch flatwork finishers are offered in finished widths of 55, 63, 75, 78, 98 and 126" meaning there's a size to fit the needs of any size laundry.

Excellent efficiency.

Thick, polished steel cylinders maintain more even heat (compared to the thinner cylinders of competing models) and help make the finishers highly efficient. A totally enclosed cabinet also contributes to its energy efficiency.